

Lanyard

EAL10102

CE Certificate EN354
Production Control: Module D

- Made up of dia. 13mm polyester twisted rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Spliced end is protected with a strong transparent covering sleeve.
- Colored tracer strand losing color to show the lanyard is unfit for use



EAL10102

Connectors:

Ref.	End	Other End	Length (m)
EAL10102	C1101	H1201	1.50

EAL13101

CE Certificate EN358
Production Control: Module D

- Made up of dia. 12mm polyester kernmantle rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Spliced end is protected with a strong transparent covering sleeve.
- Colored tracer strand losing color to show the lanyard is unfit for use.



H1209

B-400

Connectors:

Max. Length 2.0m (including connectors)

Ref.	End of lanyard	End of grab
EAL13101	-	-
EAL13101/A	H1209	-
EAL13101/AW	H1209/W	-
EAL13101/B	B-400	-

PT. FORZA NIAGA DAYATAMA

Head Office & Workshop :

Jl. Lingkungan Kayumanis No. 72 RT 004 RW 004

Cirimekar, Cibinong, Bogor, Jawa Barat 16917

Tel. +62-21-8371 1146

Website. www.forza-fse.co.id